MATERIAL SAFETY DATA SHEET

Form WI04-11A Rev. 1

Part Number(s): 25-131-25, 25-134-78, 25-135-00

Product Name: Essix C Plastics

Release Date: April 13, 2007

1. Product and Company Identification			
Trade Name & Synonyms	MSDS Code Number		
Type "C" + Plastic	Refer to part number		
Chemical Name	Manufacture / Distributor		
NA	GAC International Inc.		
C.A.S. Number	Address		
9010-79-1	355 Knickerbocker Ave.		
	Bohemia, NY USA 11716		
Grades or Minor Variant Identities	Information Telephone Number		
NA	1-631-419-1700		
Product Use (for Canada) NA	Emergency Telephone Number 1-631-419-1700		

2. Composition of Ingredients					
Hazardous Components	C.A.S. Number	Exposure Limits	%		
Polypropylene/ethylene copolymer	9010-79-1	NA	>95		
Stabilizers (trade secret)	NA	NA	<5		
This product is not considered a hazardous material by					
Raintree Essix according to the U.S occupational safety and					
health act definitions and regulation including the hazard					
communication standard 29CFR 1910.1200. Raintree Essix					
does not contain consider this product a controlled substance	does not contain consider this product a controlled substance				
according to Canada's WHMIS regulations.					
Threshold limit value (TLV) or permissible exposure limit					
(PEL) values are not established. This material is not					
expected to cause physiologic impairment at low					
concentration. Until a specific TLV is adopted by ACGIH					
(American conference of government hygienists) , or an					
OSHA PEL standard is issued, raintree essix suggest that this					
material be treated as a nuisance dust or particle in					
accordance with the recommendations of ACGIH.					

3. Hazard Identification

Emergency Overview

DENSPLY

Physical appearance: Translucent to white solid pellets.

Immediate concerns: Spilled material may present a slipping hazard. This product as shipped is not classified as a combustible dust however, a combustible concentration of dust may occur if fines are suspended in air. Avoid contact with strong oxidizing agents. When working with the material at elevated temperatures, the material will begin to decompose producing fames that can contain carbon dioxide, carbon monoxide, ketones, acrolein, aldehydes and other unidentifiable organic compounds that come from the breakdown of the material. Adequate room and extrude ventilation should be provided to minimize exposure.

WARNING AUTION LABELS: Burn risk-Avoid contact with molten resin. Explosion risk- Prevent accumulation of dust particles. Slipping risk-Keep walking surfaces free of spilled material. Vapor risk- Provide ventilation to avoid exposure to process vapors. Physical hazards: Spilled material may present a slipping hazard. Health hazards: None known.

		Single, Repeated, or		Acute and Chronic	
Routes of	Signs and Symptoms	Lifetime	Severity (Mild,	Health	Target
Exposure		Exposure	Moderate, Severe)	Effect(s)	Organ(s)
Eye	Irritation or redness	NA	NA	Acute: May	None
Yes				cause eye	known.
				irritation.	
Skin	N/A	NA	NA	NA	NA
Inhalation	Irritation of the nose, throat and respiratory tract	NA	NA	Acute: May	NA
Yes	irritation.			cause	
				respiratory tract	
				irritation.	
Ingestion	N/A	NA	NA	NA	NA

Product Name: Facin C. P. .

Part Number(s): 25-131-25, 25-134-78, 25-135-00

Release Date: April 13, 2007

Other	NA	NA	NA	NA	NA
Medical Con	ditions Aggravated by Exposure				
None known.					
Carcinogenic	city (IARC, NTP)				
This product i	s not considered to be a carcinogen by OSHA, IARC or N7	P. Irritancy: None	known. Sensitization: No	one known.	
Subtonic/chro	nic toxicity: Chronic: None known. Teratogenicity: None k	nown. Reproducti	ve toxin: None known. M	lutagenicity: None k	nown.
Potential Environmental Effects					
Potential health effects: Inhalation: Remove to fresh air. If breathing is difficult or has stopped, administer artificial respiration (mouth-to-mouth)					
or oxygen is indicated. Call a physician. Skin: Exposure to molten resin may cause thermal burns. Ingestion: None known. Inhalation: None					
known.					

Routes of Exposure	First Aid Instructions	Immediate Medical Attention	Delayed Effects
Eye	Flush eye with water for 15 minutes.	Get medical attention.	NA
Skin	If molten material comes in contact with the skin, cool under ice water or a running stream of water. Do not attempt to remove the material from the skin. Removal could result in severed tissue damage.	Get medical attention.	NA
(nhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficulty, give oxygen.	Give medical attention.	NA
Ingestion	Not applicable.	NA	NA
Other	NA	NA	NA

None. Antidotes: N/A. Additional information: None

5. Fire and Explosion Data					
Flashpoint & Method: °C / °F N/D	Flammable (Explosive) Limits in A LEL: N/D UEL: N/D	ir Autoignition Temperature N/D	Other Sensitive to static discharge:		
Flame Propagation or Burning Hazardous combustion products: Carbon monoxide, carbon dioxide, ketones, acrolein, aldehydes, and unidentified organic compounds. Properties Contributing to Fire Intensity NA		Flammability Classification Health-1, Flammability-0, Reactivity-0.	Static discharge could be in ignition source for a combustible concentration of dust. Sensitivity to impact: N/A		
Extinguishing Media		Extinguishing Media to Avoid			
Use alcohol, foam, carbon dioxide, or water spray when fighting fire involving this material.		NA			
Protection and Procedures for	or Firefighters				
	s A fires. Fire fighting equipment: As equivalent) and full protective gear.	in any fire, wear self-contained pressure demar	nd breathing apparatus,		
Unusual Fire and Explosion	Hazards				
Product as shipped is not a con	mbustible dust. However, a combustible	e concentration of dust may occur when fires a	re suspended in air.		

MATERIAL SAFETY DATA SHEET

Part Number(s): 25-131-25, 25-134-78, 25-135-00

Product Name: Essix C Plastics

Release Date: April 13, 2007

6. Accidental Release Measures

Containment Techniques

Environmental precautions: Water spill: Keep pellets out of waterways. Land spill: Not yet determined. Air spill: Not yet determined.

Spill/Leak Clean-Up Procedures and Equipment

Small spill: Vacuum or sweep up material and place in a disposal container.

Large spill: Vacuum or sweep up material and place in a disposal container.

Eyewash fountains and safety showers should be easily accessible.

Evacuation Procedures

Special Instructions

Vacuum or sweep up material and place in a disposal container. Release notes: None. Special protective equipment: None

Reporting Requirements

NA

7. Handling and Storage

Handling Practices and Warnings

Storage Practices and Warnings

(C/F). NA

8. Exposure Control/Personal Protection				
		Other Engineering C	ontrols	
extrude to minimize	om ventilation. Provide adequate ventilation at the exposure to process vapors. Eliminate ignition r and maintenance operations.	ne NA		
Routes of Entry:	Personal Protective Equipment (PPE) for Norm	nal Use:	PPE for Emergencies:	
Eye/Face	Wear safety glasses with side shields or goggles.		NA	
Skin	When handling and/or processing resins at elevated temperatures or in a molten state, wear protective clothing over the skin to prevent contact. Protective clothing: When handling and /or processing resins at elevated temperatures or in a molten state, wear protective clothing over the skin to prevent contact.		NA	
Inhalation	A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.		NA	
General Hygiene Considerations and Work Practices				
N/E				
Protective Measures During Repair and Maintenance of Contaminated Equipment				
NA				
Other Protective M	leasures and Equipment			

DENSPLY MATERIAL SAFETY DATA SHEET Form WI04-11A Rev. 1

Part Number(s): 25-131-25, 25-134-78, 25-135-00

Product Name: Essix C Plastics

Release Date: April 13, 2007

Q Phy	sical and Chemica	l Character	istics
Appearance		ii Character	Odor
Physical state: Solid (film or sheet) Color: Translucent to white. Appearance: Pellet.			Slight waxy odor
Normal Physical State:	Normal Physical State:		
☐ Liquid ☐ Gas			Melting Point 120°C / >248
Solid (Other)			
Specific Gravity or Density (H ₂ 0=1)	C-1-1:1:4 : XV-4		Freezing Point °C / °F N/A
0.88 to 0.92	Solubility in Water N/A	pH N/A	
Vapor Pressure (mm Hg @ 20°C)	Vapor Density (AIR= 1)		poration Rate (Butyl Acetate = 1)
N/A	N/A	N/A	
Other	10/11	11/2	1
Density: N/D Viscosity: N/A VOC notes: Not y	et determined. Percent volatile: <	<0.4%. Physical state: 1	None. Molecular weight: N/A
			g
10	. Stability and Re	activity Data	ล
Incompatibility (Materials to Avoid)	· Stability and ite	activity But	•
Oxidizing materials.			
Hazardous Products Produced During Decor	nposition		
At elevated temperatures the material will begin acrolein, aldehydes, and unidentified organic co		that can contain carbon	dioxide, carbon monoxide, ketones,
Hazardous Polymerization? Conditions to Avoid			
☐ May Occur ☐ May Not Oc	ccur	C / °F Will not occur	
Stability? Conditions to Avoid			
Stable ☐ Unstable °C / °F NA			
1	1. Toxicological I	nformation	
Toxicity Data, Epidemiology Studies, Carcin	ogenicity, Neurological Effects,	Genetic or Reproduc	tive Effects, or Structure Activity Data
Environmental data: N.A			
Ecotoxicological information: N.A			
Distribution: N.A			
Chemical fate information: Not readily biodegra	adable.		
	12. Ecological In		
Toxicity, Environmental Fate, Physical/Chem	nical Data, or Other Data Supp	orting Environmental	Hazard Statements

DENSPLY MATERIAL SAFETY DATA SHEET Form WI04-11A Rev. 1

Part Number(s): 25-131-25, 25-134-78, 25-

135-00

Release Date: April 13, 2007

Product Name: Essix C Plastics

13. Disposal Considerations				
Regulations				
Disposal method: 1. Recycle (reprocess)				
2. Incineration including energy recovery of waste material in a permitted facility in accordance with local, state or provincial and/or federal regulations.				
industrial waste in some state or provinces. or (f), i.e., chemical products that are considerable to the control of the contr	ged to be a hazardous waste by any local, state or for This product is not listed in the U.S. federal hazard dered hazardous if they become wastes. It does not azardous waste regulations may apply if different fr	ous waste regulations exhibit any of the haz	, 40 CFR 261.33 paragraphs (e)	
Properties (Physical/Chemical) Affecting	Disposal			
NA				
	14. Transport Informati	on		
Regulated for shipping?	Proper Shipping Name	Packing Group		
Yes No NA	Essix C Plastics	NA		
Do changes in quantity, packaging, or sh	ipment method change product classification?	Hazard Class	Identification Number	
Yes No NA	-Pinone monou change product changementon	NA	NA	
	15. Regulatory Informat	ion		
F-dl Dl-d	15. Regulatory Illiorillat	1011		
Title TSCA	A title III (Superfund amendments and reauthorizat III notes: This product is not subject to SARA title A Status: This product appears on the TSCA.	III requirements.	AU2O 45 OSUA	
definitions.	A hazard comm. rule: Raintree essix does not judge	tnis product nazardou	s according to OSHA	
	Clean water act: This product is regulated under EPA's clean water act/NPDES rules as floating material. In addition, this product is considered significant material under EPA's storm water permit rules.			
International Regulations Regulatory information Canada: WHMS: This product is not considered a controlled substance under WHMS. This MSDS meets WHMS format requirements.				
Canadian environmental protection act: All ingredients in this product are listed under CEPA on the DSL. Regulations: International regulations: All ingredients are in compliance with EINECS/ELINCS.				
Other				
NA				
	16. Other Information	 1		
Supplier Number: 40/25	Supplier Release: NA			
	ailable, $\mathbf{N}/\mathbf{E} = \text{not established. } \mathbf{N}/\mathbf{D} = \text{not}$	determined.		